



Product Service

CERTIFICATE

No. Z1A 015912 0052 Rev. 01

Holder of Certificate: Ebara Pumps Europe S.p.A.

Via Campo Sportivo 30
38023 Cles (TN)
ITALY

Certification Mark:



Product:

Submerged pump

Tested according to:

EN 60335-2-41:2021/A11:2021
EN 60335-1:2012/A15:2021
AfPS GS 2019:01 PAK
EN 62233:2008

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.:

ELS1586118A.01

Valid until:

2029-02-06

Date,

2024-02-08

(Massimiliano Mortellaro)

CERTIFICATE

No. Z1A 015912 0052 Rev. 01

Model(s):

BEST/A 2 H07RN8-F	– cod. 1721094604A
BEST/A 2M A H07RN8-F	– cod. 1721094621A
BEST/A 2M H07RN8-F	– cod. 1721094721A
BEST/A 3 H07RN8-F	– cod. 1721104604A
BEST/A 3M A H07RN8-F	– cod. 1721104621A
BEST/A 3M H07RN8-F	– cod. 1721104721A
BEST/A 4 H07RN8-F	– cod. 1731154604A
BEST/A 4M A H07RN8-F	– cod. 1731154621A
BEST/A 4M H07RN8-F	– cod. 1731154721A
BEST/A 5 H07RN8-F	– cod. 1731204604A

Brand Name:**EBARA**

Rated input voltage:	230-240 VAC 1ph, 400-415 VAC 3ph
Rated frequency:	50 Hz
Rated input power:	See table
Rated input current:	See table
Maximum water temperature:	35 °C
Maximum submersion depth:	See table
Protection class:	I
Degree of protection:	IP68



CERTIFICATE

No. Z1A 015912 0052 Rev. 01

Code	Model	Rated Voltage	Rated Power (P1) [kW]	Rated current [A]	Max head [m]	Min head [m]	Maximum depth [m]
1721094604A	BEST/A 2 H07RN8-F	400-415 V 3ph	1.0	2	13.1	2.9	7
1721094621A	BEST/A 2M A H07RN8-F	230-240 V	0.98	4.4	13.1	2.9	7
1721094721A	BEST/A 2M H07RN8-F	230-240 V	0.98	4.4	13.1	2.9	7
1721104604A	BEST/A 3 H07RN8-F	400-415 V 3ph	1.2	2.4	14.6	3.2	7
1721104621A	BEST/A 3M A H07RN8-F	230-240 V	1.3	5.6	14.6	3.2	7
1721104721A	BEST/A 3M H07RN8-F	230-240 V	1.3	5.6	14.6	3.2	7
1731154604A	BEST/A 4 H07RN8-F	400-415 V 3ph	1.6	3.0	18	4.6	7
1731154621A	BEST/A 4M A H07RN8-F	230-240 V	1.65	7.3	18	4.6	7
1731154721A	BEST/A 4M H07RN8-F	230-240 V	1.65	7.3	18	4.6	7
1731204604A	BEST/A 5 H07RN8-F	400-415 V 3ph	1.7	3.3	19	5	7